PACIFIC Lever Blocks

The New Pacific Lever Block has a superior new design and with all the new features still boasts being one of the most

FEATURES


Australian market.


- New "T" type hooks for improved load holding integrity (except 250kg)
- New design double pawl safety springs to eliminate sticking
- New style cast hand wheel for added strength and durability
- Key internal components are CNC machined before being heat treated and toughened
- New brake lockout bearing for improved security of braking mechanism
- Fitted with high quality European zinc plated Grade 80 load chain
- Overall better design and improved finish to prolong life expectancy
- No aluminium content ensures suitability for mining applications
- Overall better design and improved finish to prolong life expectancy


Better Quality Easier to Use **Improved Safety Lower Cost**



Dimensions







Specifications

Rated Capacity	250kg	500kg	800kg	1.6 tonne	3.2 tonne	6.3 tonne
Stock Code	PLB302	PLB305	PLB308	PLB316	PLB332	PLB363
Standard Lift	n 1.5	1.5	1.5	1.5	1.5	1.5
Test Load	g 375	750	1200	2400	4800	9450
Effort required to lift full load	N 115	248	285	315	360	370
No load chain falls	1	1	1	1	1	2
Load Chain mm x m	m Ø4x12	Ø5 x 15	Ø5.6X17	Ø7.1X21	Ø10X28	Ø10X28
Head room m	m 235	310	340	400	520	640
Length of lever handle m	m 168	253	273	378	418	418
Dimensions mm	A 100	143	147	173	200	200
	B 70	85	87	99	112	112
	C 86	118	132	145	198	230
	Ø 18	20	25	30	36	43
	E 20	22	26	29	37	43
Net Weight	cg 2.4	3.7	7	10	20	31

Your nearest distributor;

The information contained herein is to be used as a guide only, specifications subject to change without notice.

All Materials Handling/Lifting jobs should be assessed individually. Pacific Hoists products are NOT to be used for lifting or lowering person/s.

